

Description:

Unicoate Wood stain is a solvent based combined of oil based and micronized dyes designed for colouring All types of New Wood interior surfaces such as floors and furniture.

Surface Preparation and Application Method:

1. The surface should be dry, and free from dirt, oil, grease, and powdery material.
2. For new wood, sand the entire surface until completely smooth.
3. Apply **Unicoate Wood stain** with a soft brush , spray or a rag in the direction of the grain, let the stain penetrates deep for 7 to 10 minutes to be sure to obtain the desired colour.
4. After drying, apply second coat of the stain in the same direction.
5. Apply two coats of **Unicoate NC Sanding Sealer** or **Unicoate PU Sealer** by cross-coat technique in order to obtain a high build and ensure optimum spreading.

Features:

1. For only interior use
2. Fast drying
3. Wide range of colours
4. Excellent Workability
5. Tough and flexible finish
6. Excellent anchoring to the surface

Dilution and Application:

Type of thinner	: Unicoate Turpentine and NC thinners
Percentage of thinning	: depends on the colour required
Tools	: soft brush ,cotton, rag and spray gun
Mixing	: Hand mixing with a paddle, don't shake

Drying time (at 25C):

Touch dry	: Maximum - 15 minutes
Hard dry	: Maximum - 30 minutes

Physicals Properties:

Finish	: Satin
Flash Point	: 35 C
Specific Gravity	: 0.84 - 0.88 kg/L
Solid by Weight	: Approx. 20 - 30%
Coverage rate	: 20 – 30 m ² /L
Dry film thickness	: 20 - 50 microns
Shelf Life (dry and cool store)	: Two years

Packing:**4.0 L Gallon****1 L****Colors:**

Wood Stain colour card

Subsequent Coats:

Unicoate Sealers

Remarks:

Before Application

- Stir thoroughly
- Check Temperature above 7 C and relative humidity less than 80%

After Application

- Clean all tools used immediately with NC Thinner
- Close the cans after use
- Store in a dry and cool area

For more information, don't hesitate to contact our Technical Department.**UNICOATE FOR INDUSTRY****New industrial Area-Doha Qatar****TEL: +974-40399272 Email: info@unicoate.com www.unicoate.com**